## **FOAM**

Badger's unique line of portable foam fire extinguishers contain an alcohol resistant (AR) type of aqueous film-forming foam (AFFF). They are specifically formulated for optimum performance in a hand portable fire extinguisher. This means when sufficiently applied, Universal Ultra's vapor sealing capability can actually prevent a fire from happening.

Badger foam units are effective on Class A common combustibles as well as hydrocarbon and polar solvent types of Class B flammable liquids, so they eliminate the application guesswork often associated with other foams. The unique synthetic base of Universal Ultra foam has no offensive odor, is non-toxic, environmentally-friendly, biodegradable and extremely simple to use and clean up.

## **FEATURES**

- Plated brass valves with stainless steel handle and lever
- Large, easy-to-pull stainless steel ring pin
- Heavy-duty machined and anodized aluminum air aspirating nozzle
- Suppresses flammable liquid vapors to prevent re-ignition
- UL Listed—Meets DOT requirements
- AR-AFFF Foam works on both hydrocarbon and polar solvent types of liquid fuels
- Full stainless steel cylinder and base
- Hex valve collar tightening ring for easy recharge
- Six-year limited warranty

Unit shipped empty with concentrate. Recharge after purchase.

Agent	AR-AFFF Foam
Model	F-250-1
P/N	23697
Nominal Capacity	2.5 gal / 9.46 liter
UL Fire Rating	1-A:30-B
Cylinder Material	Stainless Steel
Valve Material	Plated Brass
Handle/Lever Mat	Stainless Steel
Recharge Expellant	Nitrogen/Air
Operating Pressure	100 @70°F
Nom Agent Flow Rate (sec)	0.27 lb / .12 kg
Discharge Range	10-15 ft / 3-4.6 m
Nom Discharge Time	90-110 sec
Height (in / cm)	24.5 / 62.2
Width (in / cm)	8.75 / 22.2
Depth (in / cm)	7 / 17.8
Shipping Wgt	12 lb / 5.4 kg
USCG Approval	N/A
Bracket	UB-20(opt)
Recharge	F-250, P/N: 23702

This information is subject to change without notice. Badger Fire Protection disclaims any liability for any errors or misinterpretations of the information contained therein. Contact Badger Fire Protection or your local distributor for assistance.

## ▲ WARNING:

This product contains
Perfluorooctanoic Acid (PFOA)
which is known to the State of
California to cause cancer and
birth defects or other
reproductive harm.

For more information go to www.P65Warnings.ca.gov.



Temp range: 35°F (1.7°C) to 120°F (49°C)















