

ABC Multipurpose Dry Chemical

LEADING FIRE PROTECTION FOR OVER A CENTURY

From the earliest hand helds to the iconic Badger line of dry and wet chemical extinguishers, the experts turn to Badger Fire Protection for reliable, quality built solutions.

The latest Badger Standard fire extinguishers incorporate years of customer insights and industry knowledge to address real-world challenges. Enhancements to product quality, ease of use, reliability, and serviceability combine to set a new standard in fire protection performance and customer value. All models are charged with high-grade multipurpose ABC dry chemical agent to tackle the majority of fire risks typically found in industrial, commercial, and domestic applications.

USER FEATURES

- Ergonomic, corrosion-resistant handles and levers enhance ease-of-use and durability
- Large, easy-to-read bilingual nameplates simplify product operation and servicing
- Large loop stainless-steel pull pins ensure easy removal, even with gloves on



SERVICE FEATURES

- Scannable FX EZTag QR codes centralize product data for use with digital asset management applications
- Rolled steel bases (10 and 20 lb models) improve cylinder durability, prolong service life, and reduce repair costs
- Custom hose retention bands provide secure cylinder fit, and reduce maintenance costs
- Hex hose coupling enables proper tightening and removal of hoses using standard tools
- Six-year limited warranty



Agent	Badger Multi-Purpose Commercial ABC Dry Chemical (90% MAP)				
Model	STD-2.5MP-1	STD-5MP-1		STD-10MP-1	STD-20MP-1
P/N	22430	22486	22435	22603	22682
Nominal Agent Capacity	2.5 lb / 1.1 kg	5 lb / 2.3 kg		10 lb / 4.5 kg	20 lb / 9.1 kg
UL Fire Rating	1-A:10-B:C	3-A:40-B:C		4-A:80-B:C	6-A:120-B:C
Cylinder Construction	Steel			Steel with reinforced rolled base	
Valve Body Construction	Anodized Forged Aluminum				
Handle / Lever Type	Ergonomic Anodized Aluminum			Ergonomic Stainless Steel	
Recharge Expellant	Nitrogen				
Operating Pressure	195 @ 70°F				
Temp Range	40°F (-40°C) to 120°F (49°C)				
Nom Agent Flow Rate (sec)	.31 lb / .14 kg	.39 lb / .18 kg		.51 lb / .23 kg	.75 lb / .34 kg
Discharge Range	10-15 ft / 3-4.6 m	12-18 ft / 3.7-5.5 m		16-20 ft / 4.9-6.1 m	
Nom Discharge Time (sec)	9.5	14		22	28
Height (in / cm)	14.88 / 37.79	15.25 / 38.74		19.38 / 49.22	21.38 / 54.31
Width (in / cm)	5.73 / 14.55	7.75 / 19.69		8.25 / 20.96	9.63 / 24.45
Depth (in / cm) Cylinder Diameter (in / cm)	3.53 / 8.93 3.04 / 7.72	4.25 / 10.80		5.25 / 13.34	7.25 / 18.42
Shipping Weight	5.4 lb / 2.4 kg	10 lb / 4.5 kg		17 lb / 7.7 kg	33 lb / 15 kg
USCG Approval	5-B (Type B:C Size I)	20-B (Type A Size II) (Type B:C Size I)		20-B (Type A Size II) (Type B:C Size II)	20-B (Type A Size II) (Type B:C Size III)
Mounting Bracket	MB-250 (included)	MB-5 (included)	MB-5 (optional)	UB-10 (optional)	UB-20 (optional)



This information is subject to change without notice. Badger Fire Protection disclaims any liability for any errors or misinterpretations of the information contained therein. Contact Badger Fire Protection or your local distributor for assistance.